VEHICLE TYPE: MOTOR GRADER

proudly developed by

Reduce Blind Spot Accidents


Actively Detect Objects

The in-cab display provides the driver with an audible and visual alert when an object is in the detection zone. As the object moves closer to the sensor, the audible alert increases and more LEDs light up on the display.

One Xtreme PreView® sensor is mounted on the rear of the motor grader



the in-cab display to the sensors.



PreView Coverage Area

Available Options: Replace in-cab LED display

with PreView Plus camera and monitor system. Superimposes object detection indicators directly on to monitor and will support up to 4 cameras.



www.aps-supply.com

IV.	TTA /F	$\Gamma \cap N$	CTC:	$\Gamma \cap$	NS
	II VI		V.)	11	

Xtreme Sensor: $7.4"(w) \times 2.4"(d) \times 7.6"(h)$

In-Cab Display: 2.3"(w) x 2"(d) x 1"(h)

RECOMMENDED CONFIGURATION

I Xtreme PreView Sensors set at 10M

SPECIFICATIONS

Op. Temp: $-40^{\circ} - +185^{\circ}F / -40^{\circ} - +85^{\circ}C$

Current Draw: < 1/2 AMP

To determine the best configuration to fit your specific vehicle and site conditions, please call 08 9248 4419, visit www.aps-supply.com, or email sales.apsa@aps-supply.com to speak to a Blind Spot specialist. miningmotorgrader2012