


BlackVue DR770X-1CH



The BlackVue DR770X-1CH Dashcam is a single-channel Full HD Sony STARVIS™ image sensor, which gives you best image quality under any light. Also included are GPS logger, Wi-Fi, Cloud connectivity, impact and motion detection. All this in a stealthy design that never gets in the way of your driving. No need for a screen: with the free BlackVue app, connect to your dashcam whenever you want.

- Full HD Recording
- High FPS Full HD Camera
- Sony STARVIS™ Sensor
- Front viewing angle
- Improved low light sensitivity
- Optional LTE connectivity module (not-included)
- Native Parking Mode Support
- Built-in WiFi with Mobile App
- Built-in Power Management
- Enhanced Night Vision

Suitable for: Commercial and private vehicles, trucks, long-haul trucks, fleet trucks, lorries, waste, utility vehicles

Quick Tech Specs

Channel	1 Channel (Front)
Colour / Size / Weight	Black / Width 118.5 mm x Height 36 mm / 103 g
Memory	microSD Card (64 GB/128 GB/256 GB)
Speaker & GPS	Built-in
LED	Security LED, Recording LED, Touch Sensor LED, Bluetooth/Wi-Fi/LTE LED
Sensor	3-Axis acceleration sensor
Battery or Capacitor	Built-in Super Capacitor

Camera + Recording

Recording Mode	Normal Recording Event Recording (Impact Detection) Manual Event Recording Parking Mode Recording (Impact and Motion Detection)
Button	Touch sensor: Trigger Manual Recording
Camera	STARVIS™ CMOS Sensor (Approx. 2.1 M Pixel)
Viewing Angle	Diagonal 139°, Horizontal 116°, Vertical 61°
Format Free	Yes (Adaptive)
Resolution/FPS	Full HD (1920x1080) @60fps Highest (Extreme): 25 Mbps Highest (12 Mbps) High (10 Mbps) Normal (8 Mbps)
Image Quality	Normal (8 Mbps)
Video Codec	H.264 (AVC)
Video File Extension	MP4

Operating

Input Voltage	DC 12V – 24V (3 pole DC Plug: (Ø3.5 x Ø1.1), MAX 1A/12V)
Current	Normal Mode (WiFi On / GPS On / 1CH) : Avg. 240mA / 12V
Consumption	Parking Mode (WiFi On / GPS Off / 1CH) : Avg. 190mA / 12V Built-in Variable Voltage Cut-off System
Voltage Cut-off	11.8V – 12.5V 22.8V – 24V
Operating & Storage Temp.	-20°C – 80°C (-4°F – 176°F)
High Temp. Cut-off	Approximately 80°C (176°F)

Part No.	Description
DR770X-1CH	BlackVue DR770X-1CH

Authorised Importer and Master Distributor

APS USA
sales@aps-supply.com
P: 1 619 263 4164

APS Australia
sales.apsa@aps-supply.com
P: 61 (8) 9302 2369 (WA)
P: 61 (02) 4915 6781 (NSW)

APS Colombia
ventascolombia@aps-supply.com
T: 57 (4) 444 7275

APS Chile
ventaschile@aps-supply.com
T: 56 (2) 2948 8044

APS Perú
ventasperu@aps-supply.com
T: 56 (2) 2948 8044

APS Indonesia
techcenter@aps-supply.com

