


LW400 Series LED Linear Walkway Light







40mm Ø Pole (spigot) mounting bracket



Description

The LW400 Series LED linear walkway light is designed for the walkways of large-scale port cranes, conveyor systems and power stations. Outputting an impressive 2200 Lumens from only 20W, it features a one-for-one replacement for 70W HID lights. When used with the flat (bulkhead) mount, this light can be used as an LED replacement of fluorescent and bulkhead lighting, whilst the pole (spigot) mount can be used as an LED replacement for conveyor and pathway lighting. The LW400 is also suitable as an auxiliary light that can be affected by severe weather conditions.

Features

- · Industrial-grade LED chips and driver
- · One-for-one replacement for 70W HID fixtures
- · Tempered glass effective against aging and colour-changing
- · IP65 fixture, waterproof & shock resistant
- · Wide 140° optical lens provides even light distribution
- · Certificates: CE, RCM (APS Lighting & Safety E1496)

Applications

Walkways

Tech Specs

Туре	LEDs
Lumens	2200 Lu
Color Temperature	5500K-6000K
Voltage	120~277V AC (50Hz~60Hz)
Wattage	20W
Beam Angle	140° optical
Humidity	10% ~ 95% (no coagulation)
Operating Temperature	-30°C to +60°C
IP Rating	IP65
Housing	Forged aluminum alloy
Lens	Tempered glass
Mount	Pole (spigot) Ø 32-40mm, Flat (bulkhead)
Weight	2.2 lbs (1kg)
Dimensions (D, W, H)	Flat (bulkhead): 2.36x12.1x2.52" (60x307x64mm) Pole (40mm ø): 4.25x12.1x2.52" (108x307x64mm)

 Part No.
 Beam
 eLumens
 Voltage
 Watts
 Mount

 NAH-LW400-BP-20
 140°
 2200 Lu
 120~277V AC
 20W
 40mm ø Pole (spigot) mount bracket plus Flat (bulkhead) bracket. 5m Int. cable



Spigot Ø 32-40mm



APS USA sales@aps-supply.com P: 1 619 263 4164

aps-supply.com

(⊕)

APS Australia sales.apsa@aps-supply.com P: 61 (8) 9302 2369 (WA) P: 61 (02) 4915 6781 (NSW)

(in) APS Lighting & Safety

APS Colombia ventascolombia@aps-supply.com T: 57 (4) 444 7275

APS Chile ventaschile@aps-supply.com T: 56 (2) 2948 8044 Authorised Importer and Master Distributor

APS Perú ventasperu@aps-supply.com T: 56 (2) 2948 8044

APS Indonesia techcenter@aps-supply.com

